



REF: 03B802X09E0
✓ CE (EMC), □ UL, □ CE (LVD)

BM802

1000AAC AUTO-RANGING DIGITAL CLAMPMETER

- 3 3/4 digits LCD display, max. reading 3999
- Versatility of use with AC/DC voltage & current, resistance, capacitance, frequency (up to 20MHz) and pulse duty measurement
- Relative measurement
- Data hold, auto-power off
- Safety as per IEC1010-1 CAT.II 1000V

Technical specifications

DCV: 400m/4/40/400/1000V, $\pm 0.8\%$

ACV: 400m/4/40/400/700V, $\pm 1.2\%$

DCA: 40m/100mA, $\pm 2.0\%$

ACA: 40m/100mA, $\pm 1.0\%$ (optional)
4/40/400/1000A, $\pm 1.9\%$

OHM: 400/4k/40k/400k/4M/40M Ω , $\pm 1.0\%$

CAP: 40n/400n/4 μ /40 μ /100 μ F, $\pm 3.0\%$

FREQ: 40/400/4k/40k/400k/4M/20MHz, $\pm 0.5\%$

Pulse duty: 0.1%~99.9%

Audible continuity & diode test

Clamp size: 54mm (max.)

Battery: 1.5Vx2, AA size

Dimensions & weight: 248x88x45mm, 360g

Accessories: carrying bag

inometer