



CM206B True RMS

600A AC DIGITAL CLAMP METER

- 6,000 counts clear LCD display with backlit
- Non-Contact AC voltage detection (**NCV**)
- **LowZ** (300k Ω input impedance) and **LPF** (low-pass filter) for AC measurement
- **True RMS**, Min/Max value measurement
- Data hold, clamp work light
- Auto /manual range, auto power off
- Safety as per IEC1010-1 **Cat.III 600V**

Technical specifications

DCV: 600m/6/60/600V, $\pm 0.5\%$

ACV: 6/60/600V, $\pm 0.8\%$ (10Hz~1kHz)

ACA: 60/600A, $\pm 2.5\%$ (40Hz~1kHz)

OHM: 600/6k/60k/600k/6M/60M Ω , $\pm 1.0\%$

CAP: 10n/100n/1 μ /10 μ /100 μ /1m/10m/100mF, $\pm 4.0\%$

FREQ: 10/100/1k/10k/100k/1M/10MHz, $\pm 1.0\%$
0~100kHz, $\pm 1.0\%$ (ACV, ACA)

Duty Cycle: 1%~99%, $\pm 3.0\%$

TEMP: -40 $^{\circ}$ C~1000 $^{\circ}$ C, -40 $^{\circ}$ F~1832 $^{\circ}$ F, $\pm 1.0\%$

Audible continuity (<30 Ω) & diode test

Clamp size: 26x44mm

Battery: 1.5Vx2, AAA size

Dimensions: 193x73x34mm, 260g approx.

Accessories: carrying bag

REF: 03H206B0000

☑ CE (EMC), ☐ UL, ☐ CE (LVD)