



## CM208A True RMS

### 1000A AC DIGITAL CLAMP METER

- 6,000 counts color LCD display with backlit
- Non-Contact AC voltage and live wire detection
- VFD (variable-frequency), LowZ (300k $\Omega$  input) and Inrush current measurement
- True RMS, Min/Max & relative measurement
- Data hold, clamp work light
- Auto /manual range, auto power off
- Safety as per IEC1010-1 **Cat.III 1000V & Cat. IV 600V**

#### Technical specifications

DCV: 600m/6/60/600/1000V,  $\pm 0.5\%$

ACV: 600m/6/60/600/750V,  $\pm 0.8\%$  (40Hz~1kHz)

ACA: 60/600/1000A,  $\pm 2.5\%$  (40Hz~400Hz)

OHM: 600/6k/60k/600k/6M/60M  $\Omega$ ,  $\pm 0.8\%$

CAP: 10n/100n/1 $\mu$ /10 $\mu$ /100 $\mu$ /1m/10m  
/100mF,  $\pm 3.0\%$

FREQ: 10/100/1k/10k/100k/1M/10MHz,  $\pm 0.5\%$   
10~10kHz(ACV), 10~1kHz(ACA)

Duty Cycle: 1%~99%,  $\pm 1.0\%$

TEMP: -40 $^{\circ}$ C~1000 $^{\circ}$ C, -40 $^{\circ}$ F~1832 $^{\circ}$ F,  $\pm 1.0\%$

Audible continuity (<30  $\Omega$ ) & diode test

Clamp size: 35x60mm

Battery: 1.5Vx3, AAA size

Dimensions: 240x85x47mm, 380g approx.

Accessories: carrying bag

REF: 03H206D0000

☑ CE (EMC), ☐ UL, ☐ CE (LVD)

inometer