



CM208D True RMS

1000A AC/DC DIGITAL CLAMP METER

- 6,000 counts color LCD display with backlight
- Non-Contact AC voltage and live wire detection
- VFD (variable-frequency), LowZ (300k Ω input) and Inrush current measurement
- True RMS, Min/Max & relative measurement
- Data hold, clamp work light
- DCA zero adjust, auto range, auto power off
- Safety as per IEC1010-1 **Cat.III 1000V & Cat. IV 600V**

Technical specifications

DCV: 600m/6/60/600/1000V, $\pm 0.5\%$

ACV: 600m/6/60/600/750V, $\pm 0.8\%$ (40Hz~1kHz)

DCA: 60/600/1000A, $\pm 2.5\%$

ACA: 60/600/1000A, $\pm 2.5\%$ (40Hz~400Hz)

OHM: 600/6k/60k/600k/6M/60M Ω , $\pm 0.8\%$

CAP: 10n/100n/1 μ /10 μ /100 μ /1m/10m
/100mF, $\pm 3.0\%$

FREQ: 10/100/1k/10k/100k/1M/10MHz, $\pm 0.5\%$
10~10kHz(ACV), 10~1kHz (ACA)

Duty Cycle: 1%~99%, $\pm 1.0\%$

TEMP: -40 $^{\circ}$ C~1000 $^{\circ}$ C, -40 $^{\circ}$ F~1832 $^{\circ}$ F, $\pm 1.0\%$

Audible continuity (<30 Ω) & diode test

Clamp size: 35x60mm

Battery: 1.5Vx3, AAA size

Dimensions: 240x85x47mm, 380g approx.

Accessories: carrying bag

REF: 03H206D0000

☑CE (EMC), ☐UL, ☐CE (LVD)

Sinometer