

CP-W96, CP-Var96

POWER METER (MOVING COIL)

CP-W96, CP-Var96: 96x96mm, 240°/90°

CP-W80, CP-Var80: 80x80mm, 240°/90°

CP-W72, CP-Var72: 72x72mm, 240°/90°

CP-W48, CP-Var48: 48x48mm, 240°/90°



REF: 12CP0W0000

✓ CE (EMC), UL, CE (LVD)

- For measuring active or inactive power of single or three phase network
- Self extinguished, dust & splash proof plastic housing with back cover
- Complee™ vibration proof double-jewel bearing ensure long-term damping
- Complee™ movement with improved linearity, overshoot <15%
- Low temperature efficient, operates at room temperature from -25°C to 40°C
- Interchangeable dial with printed scales
- Equipped with zero adjustment knob
- Insulation: 2000V/50Hz, 1min
- Conforms to IEC51, IEC473 & IEC1010

Technical Data:

Basic accuracy: class 1.5

Direct input:

Single phase 100/220/380V

3P3W 100/220/380/415V

3P4W 100/220(380)/240(415)V

CT input: 380/100V, 500/100V, 3k/100V,

6k/100V, 10k/100V, 15k/100V,

35k/100V, Secondary /1A, /5A

Frequency: 50/60Hz

Mounting: by nuts, max. depth 43mm

External convertor: 72x72mm or 96x96mm