

D48AV SERIES

DIGITAL AMMETER & VOLTMETER

- 3 1/2 digits LED display (0.5 inch), maximum reading 1999
- Auto polarity and overload indication
- Both AC, DC models available
 - D48A:** ammeter, **D48V:** voltmeter
 - D48AV:** ammeter/voltmeter 2 in 1 (display switchable)
- Conforms to IEC1010 standard



REF: 12D48AV1100/1100/13C0
✓ CE (EMC), UL, CE (LVD)

Technical Specifications

Dimensions: 96x48mm

Basic accuracy: $\pm 0.5\%$

Operating temperature: -10° to 50°C

Dielectric strength: AC 2kV / 1 Min

Isolation resistance: DC 500V, 100M

Measuring range:

AC Current: set by DIP switch
60/5A, 100/5A, 150/5A, 200/5A,
250/5A, 300/5A, 400/5A,
500/5A, 600/5A, 750/5A,
800/5A, 1000/5A, 1200/5A,
1500/5A, 1999/5A

DC Current: set by DIP switch
1999mA, 1.999mA, 19.99mA,
199.9mA, 1.999A, 15A

AC Voltage: 0-600V

DC Voltage: Set by DIP switch
199.9mV, 1.999V, 19.99V,
199.9V, 750V

Aux. power:

AC 110V/220V 50/60Hz

DC 12V, 18V, 24V (optional)

Consumption: <1.8VA

Sinometer