## DM112A True RMS SMART MOBILE-PHONE DMM LARGE SCREEN



- 2000 counts large screen LCD display with backlit and function/unit indicators
- Button operation
- Smart (auto-function) & auto-ranging 2 in 1
   Non-contact AC voltage (NCV) test
- Live wire detection
- Fuse broken warning, input jack warning
   True RMS AC measurement (40Hz~1kHz)
- Built-in torch lamp on back
- Data hold, auto power-off
   With holster and back stand, safety as per IEC1010-1 Cat.III 600V

Technical specifications
DCV: 2/20/200/600V, ±0.5%
0.8V-600.0V (smart), ±0.5%
ACV: 2/20/200/600V, ±1.0% (40Hz~1kHz)
0.5V-600.0V (smart), ±1.0%
DCA: 20m/200m/600mA, ±1.2%
ACA: 20m/200m/600mA, ±1.5% (40Hz~1kHz)
OHM: 200/2k/20k/200k/20k/20M2 0. ±1.0%:

 $0.5\,\Omega$  ~6k $\Omega$  (smart),  $\pm 1.0\%$ Continuity (<50 $\Omega$ ) & diode test (2.0V) NCV: two levels, buzzer & L/H indication Dimensions: 68x133x19mm, 130g approx. Battery: 3Vx2, CR2032

sinometer sinometer