

DM112B True RMS

SMART MOBILE-PHONE DMM
LARGE SCREEN



- 6000 counts large screen LCD display with backlit and bar-graph
- Button operation with function/unit indicators
- Auxiliary frequency display on AC ranges
- Smart (auto-function) & auto-ranging 2 in 1
- Non-contact AC voltage (NCV) test
- Live wire detection
- Fuse broken warning, input jack warning
- True RMS AC measurement (40Hz~1kHz)
- Built-in torch lamp on back
- Data hold, auto power-off
- With holster and back stand, safety as per IEC1010-1 Cat.III 600V

Technical specifications

- DCV: 60m/600m/6/60/600V, $\pm 0.5\%$
0.8V~600.0V (smart), $\pm 0.5\%$
- ACV: 60m/600m/6/60/600V, $\pm 1.0\%$ (40Hz~1kHz)
0.5V~600.9V (smart), $\pm 1.0\%$
- DCA: 6000 μ /60m/600mA, $\pm 1.2\%$
- ACA: 6000 μ /60m/600mA, $\pm 1.5\%$ (40Hz~1kHz)
- OHM: 600/6k/60k/600k/6M/60M Ω , $\pm 1.0\%$;
0.5 Ω ~6k Ω (smart), $\pm 1.0\%$
- CAP: 6n/60n/600n/6 μ /60 μ /600 μ /6m/60mF, $\pm 5.0\%$
- FREQ: 10/100/1k/10k/100k/1M/10MHz, $\pm 1.0\%$
30Hz~2kHz (from ACV), 10Hz~2kHz (from mA)
- Pulse duty: 1.0~99.0%, $\pm 3.0\%$
- Continuity (<50 Ω) & diode test (2.0V)
- NCV: two levels, buzzer & L/H indication
- Dimensions: 68x133x19mm, 130g approx.
- Battery: 3Vx2, CR2032

REF: 01HT112B0000
☑ CE (EMC), ☐ UL, ☑ CE (LVD)

