

DM625B DIGITAL ANEMOMETER

- 9999 counts color LCD display
- Measuring air velocity, air flow volume, air temperature and humidity, dew point and wet-bulb temperature
- Air duct area setting
- Air velocity in m/s, km/h, mph, ft/m, ft/s, knots, bft;
Air flow in CFM (ft³/min), CMM (m³/min) or CMS (m³/s);
Air temperature in °C or °F
- USB interface to computer
- Data hold, Max /Min /Avg value measurement
- Overflow and low battery indication
- Auto power-off (about 10 minutes)

Technical specifications

Air velocity: 0.40~30.00 m/s, 1.40~108.0 km/h,
1.30~98.50 ft/s, 0.80~58.30 knots,
0.90~67.10 mph, 78.00~5900 ft/m, ±2.0%; 0~12 bft

Air flow: 0~9999 (CFM, CMM, CMS) (air duct area 0~9.999)

Air temperature: -20.0°C~60.0°C (-4.0°F~140.0°F), ±1.5°C

Dew point: -50.0°C~60.0°C (-58.0°F~140.0°F), ±1.5°C

Wet bulb: -20.0°C~60.0°C (-4.0°F~140.0°F), ±1.5°C

Air humidity: 5%~95%RH, ±4.0%RH

Response time: 0.5s

Battery: 1.5Vx3, AAA

Dimensions: 197x60x33mm, ~ 180g

REF: 03H625B0000

CE (EMC), UL, CE (LVD)

Sinometer

