



DM9804A+

GENERAL PURPOSE DMM with BACKLIT

- 3 1/2 digits jumbo LCD display with unit annunciator, max. reading 1999
- Data hold and LCD backlit
- Enhanced protection on all ranges and against electro-magnetic interference
- Auto-power off (approx. 30 min)
- Integrated holster, shock-proof design
- Safety as per IEC1010-1 Cat.II 1000V

Technical specifications

DCV: 200m/2/20/200/1000V, $\pm 0.5\%$

ACV: 2/20/200/750V, $\pm 0.8\%$ (40~400Hz)

DCA: 20m/200m/20A, $\pm 0.8\%$

ACA: 20m/200m/20A, $\pm 1.0\%$

OHM: 200/2k/20k/200k/2M/200M, $\pm 0.8\%$

CAP: 20n/200n/20 μ /2000 μ F, $\pm 2.0\%$

FREQ: 2k/200kHz, $\pm 3.0\%$

TEMP: -40 ~ 1000, $\pm 1.0\%$

Audible continuity: <30 ± 10

Transistor h_{FE} & diode test

Battery: 9Vx1, 6F22

Dimensions & weight: 185x93x35mm, ~290g

Accessories: holster, temp probe

REF: 019804A0000

✓ CE (EMC), UL, CE (LVD)

Sinometer