



DM99

AUTO-RANGE DMM WITH BAR GRAPH

- 6000 counts large LCD display with 60-segment high speed bar graph
- Max/min and relative measurement
- Data hold, auto-power off (approx. 15 min)
- Enhanced protection on all ranges and against electro-magnetic interference
- New streamline housing, integrated holster, shock-proof design
- Safety as per IEC1010-1 Cat.II 1000V

Technical specifications

DCV: 600m/6/60/600/1000V, $\pm 0.5\%$
 ACV: 600m/6/60/600/750V, $\pm 0.8\%$ (40~400Hz)
 DCA: 600 μ /6m/60m/600m/6/20A, $\pm 0.8\%$
 ACA: 600 μ /6m/60m/600m/6/20A, $\pm 1.5\%$
 OHM: 600/6k/60k/600k/6M/60M, $\pm 0.8\%$
 CAP: 40n/400n/4 μ /40 μ / 400 μ /2000 μ F, $\pm 3.5\%$
 FREQ: 100/1k/10k/100k/1M/60MHz, $\pm 0.5\%$
 TEMP: -20°C~1000°C ($\pm 0.75\%$); 0~1832°F ($\pm 1.2\%$)
 Duty cycle: 0.1% ~ 99.9%
 Audible continuity: <30 ± 10
 Transistor h_{FE} & diode test
 Battery: 1.5Vx2, AA size
 Dimensions & weight: 185x93x35mm, ~290g
 Accessories: holster, temp probe

REF: 01VC99X0000

✓ CE (EMC), UL, CE (LVD)