

HC37A TRUE RMS 1000AAC DIGITAL CLAMPMETER



- 3 3/4 digits LCD, max. reading 3999
- True RMS AC measurement
- Capacitance, Freq. & Temp. measurement
- Data hold and LCD backlit
- Auto/manual ranging
- Over range & low battery indication
- Over load protection
- Fire-resistant ABS housing, safety as per IEC1010-1, Cat.II 1000V & Cat.III 600V

Technical specifications

DCV: 4/40/400/600V, $\pm 1.0\%$

ACV: 4/40/400/600V (40~10kHz), $\pm 1.5\%$

DCmA: 400 μ /4m/40m/400mA, $\pm 1.0\%$

ACmA: 400 μ /4m/40m/400mA, $\pm 1.0\%$

ACA: 400/1000A, $\pm 2.0\%$

OHM: 400/4k/40k/400k/4M/40M Ω , $\pm 1.2\%$

CAP: 40n/400n/4 μ /40 μ /200 μ F, $\pm 3.0\%$

FREQ: 5Hz~5MHz, $\pm 1.2\%$

TEMP: -40°C~1000°C, $\pm 1.0\%$

Audible continuity & diode test

Clamp size: ϕ 38mm (max.)

Dimensions: 215x84x52mm

Weight: approx. 380g (incl. battery)

Battery: 1.5Vx2, AA size

REF: 03HC37AX2800

✓ CE (EMC), □ UL, ✓ CE (LVD)

Sinometer