

IT-3060B, IT-3060C

DIGITAL INSULATION TESTERS

- 3 1/2 digits large LCD with a max. reading of 1999
- Test of insulation resistance up to 2000 M Ω (model **IT-3060B**) or 20G (model **IT-3060C**) at rated voltages
- High driving capacity, short circuit output 1.5mA, working output 200mA
- Data hold and LCD backlit
- Auto discharge & auto zero adjustment
- Safety Standard: IEC1010 CAT. II and pollution degree class II.



Technical Specifications

Rated Voltage:

IT-3060B: 250V/500V/1000V, $\pm 10\%$

IT-3060C: 500V/1000V/2500V, $\pm 10\%$

Measuring Range:

IT-3060B: 0~2000M Ω , resolution 1M

IT-3060C: 0~20G, resolution 10M

Basic Accuracy: $\pm 3\%+2\text{dgt}$

($\pm 5\%$ or 10% within full range)

Short Circuit Output: 1.5mA

AC Voltage Range: 0-750V, $\pm 1.5\%$

Battery Check: Yes

Insulation Resistance: 500M Ω (1000V)

Withstand Voltage: AC 2KV 50Hz 1mm

Battery: 6x1.5V AA size

Dimensions: 206x140x58mm

Weight: approx.700g (incl batteries)

REF: 042070X2900/30 00/34 00

✓ CE (EMC), UL, CE (LVD)

meter