

JTA4201, JTA4201T DIGITAL ANEMOMETERS



REF: 034201X000
✓ CE (EMC), □ UL, □ CE (LVD)

- 4 digits LCD display
- Low friction ball-bearing and carefully balanced vane results in accurate velocity measurement
- 4 display mode: m/s, km/h, ft/min, knots
- Built-in air temperature °C / °F measurement (Model JTA4201T only)
- Data hold for easy reading
- Ideal for use in checking air conditioning & heating systems, measuring air

Technical specifications

Air velocity:

0.3~40.0 m/s, $\pm 3\%+2d$

1.0~140.0 km/h, $\pm 3\%+2d$

60~7800 ft/min, $\pm 3\%+10d$

0.6~79.0 knots, $\pm 3\%+2d$

(Above 30.0m/s, 108.0km/h, 5910ft/min
& 58.3knots for reference only)

Resolution: 0.1m/s, km/h, knots or 1 ft/min

Temp.: 0~60°C, $\pm 0.8^{\circ}\text{C}+3d$,

32~140°F, $\pm 1.5^{\circ}\text{F}+3d$

Resolution: 0.1°C/0.1°F

Battery: 1.5Vx4, AA size

Dimensions: 76X168X26.5mm

Weight: 350g approx.

The logo for 'Anemometer' features a stylized orange and red circular graphic to the left of the word 'Anemometer' in a bold, orange, sans-serif font.