

M9803R

HIGH ACCURACY BENCH DMM WITH INTERFACE

- 4000 counts LCD display with **42-segment bar-graph**, **backlit** and unit annunciators
- **AC/DC powered** allows carrying to the site
- Built-in storage compartment for accessories
- **True RMS AC** current/voltage measurement
- **RS232C data interface**
- Auto-ranging and automatic polarity indication
- Capacitance & frequency measurement
- **Data hold**
- **Max/Min value & relative measurement**
- ADP measurement
- Audible continuity and diode test
- Sleep function, preserves the last measured data
- High safety design

Technical Specifications

DCV: 400m/4/40/400/1000V, $\pm 0.3\%$
ACV: 4/40/400/750V (40Hz~1kHz), $\pm 0.8\%$
DCA: 4m/40m/400m/10A (20A for 30s) $\pm 0.4\%$
ACA: 4m/40m/400m/10A (20A for 30s) $\pm 1.0\%$
OHM: 400/4k/40k/400k/4M/40M, $\pm 0.5\%$
CAP: 4n/40n/400n/4 μ /40 μ F, $\pm 2.0\%$
FREQ: 100/1k/10k/100k/600kHz, $\pm 0.1\%$
ADP: 400mV $\pm 0.3\%$, 10 digit/1mV DC
Audible continuity: ~50
Diode test: 0.6mA, 3.0V
Dimensions: 238x230x83mm, 1.3kgs
Power Supply:
AC 90~264V, 50/60Hz, <10W
DC AA, LR6 or AM3 battery 1.5Vx6



REF: 019803R6800

✓ CE (EMC), UL, CE (LVD)

Sinometer