

MS2010B

HIGH ACCURACY AC LEAKAGE CLAMP METER



- 4000 counts LCD with backlit
- Up to 10 μ A resolution!
- Clamp on frequency measurement
- Data hold, relative measurement
- Low-pass filter for main AC measurement
- Continuity check with buzzer
- Auto /manual range, auto power-off
- Conforms to IEC1010-1 CAT.III 600V

Technical specifications

DCV: 400m/4/40/400/600V, $\pm 0.8\%$

ACV: 400m/4/40/400/600V, $\pm 1.0\%$

ACA: 40m/400m/4/40/400A, $\pm 3.0\%$

OHM: 400/4k/40k/400k/4M/40M, $\pm 1.0\%$

CAP: 50n/500n/5 μ /50 μ /200 μ F, $\pm 4.0\%$

FREQ: 10/100/1k/10k/100kHz (from leads),

10/100/1kHz (from clamp), $\pm 2.0\%$

Duty cycle: 0,1%~99,9%, $\pm 3.0\%$

TEMP: -20 $^{\circ}$ C~1000 $^{\circ}$ C, $\pm 3.0\%$

Continuity and diode test

Clamp size: 31mm (max.)

Dimensions & weight: 260x92x55mm, ~400g

Battery: 1.5Vx3, AAA size

REF: 032010B0000

✓ CE (EMC), UL, ✓ CE (LVD)

Simometer