

MS2108A

400AAC/DC MINI CLAMP METER



- 4000 counts LCD, max. display 3999
- Min /Max and relative measurement
- Data hold for easy reading
- **Clamp light & LCD backlight**
- Auto/manual range, auto power off
- Secondary injection molding case, safety as per IEC1010-1 CAT.III 600V

Technical specifications

DCV: 400m/4/40/400/1000V, $\pm 0.8\%$

ACV: 400m/4/40/400/750V, $\pm 1.0\%$

DCA: 40/400A, $\pm 2.0\%$

ACA: 40/400A, $\pm 2.0\%$

OHM: 400/4k/40k/400k/4M/40M Ω , $\pm 2.0\%$

CAP: 40n/400n/4 μ /40 μ /400 μ /4mF, $\pm 4.0\%$

FREQ: 10/100/1k/10k/100k/1M/10MHz, $\pm 1.0\%$

(from test leads)

FREQ: 10Hz~10kHz, $\pm 2.0\%$ (from current clamp)

Duty cycle: 0.1% ~99.9%, $\pm 3.0\%$

Audible continuity & diode test

Clamp size: 26mm (max.)

Battery: 1.5Vx3, AAA size

Dimensions & weight: 208x78x35mm, 340g

Accessories: carrying bag

REF: 032108A0000

CE (EMC), UL, CE (LVD)

inometer