



MS2138

1000A AC/DC DIGITAL CLAMP METER

- 4000 counts LCD with 42 segments bar graph
- Versatility of use with AC/DC voltage, AC/DC current, resistance & frequency measurement
- Data hold, Max./Min. value measurement
- **Clamp light** & LCD backlight
- Auto zero key for DCA measurement
- Auto/manual range, auto power off
- Secondary injection molding case, safety as per IEC1010-1 CAT.III 600V

Technical specifications

DCV: 4/40/400/600/1000V, $\pm 0.8\%$

ACV: 4/40/400/600/700V, $\pm 1.0\%$

DCA: 400/1000A, $\pm 3.0\%$

ACA: 400/1000A, $\pm 2.5\%$

OHM: 400/4k/40k/400k/4M/40M Ω , $\pm 1.0\%$

FREQ: 4k/40k/100kHz (from test leads), $\pm 0.1\%$
40Hz~400Hz (from clamp jaw), $\pm 0.1\%$

Audible continuity & diode test

Clamp size: 42mm (max.)

Battery: 1.5Vx3, AAA size

Dimensions & weight: 225x86x33mm, 320g

Accessories: carrying case

REF: 032138X0000

✓ CE (EMC), □ UL, □ CE (LVD)

 Sinometer