

MS8205F

DMM WITH MECHANICAL PROTECTION

- 3 3/4 digits LCD display with backlit & 38-segments bar graph, max. reading 3999
- Test leadjack mechanical protection and full range overload protection
- 400A AC/DC current measurement using external current transducer (optional)
- Auto ranging, auto warning message
- Data hold, auto-power off
- Safety design as per IEC 1010 standard,

Technical specifications

DCV: 4/40/400/1000V, $\pm 0.5\%$

ACV: 4/40/400/750V, $\pm 1.2\%$

DCA: 4m/40m/400m/10A, $\pm 1.2\%$

400A (0.1mV/0.1A), $\pm 1.2\%$ (with clamp)

ACA: 4m/40m/400m/10A, $\pm 1.5\%$

400A (0.1mV/0.1A), $\pm 1.5\%$ (with clamp)

OHM: 400/4k/40k/400k/4M/40M, $\pm 1.2\%$

CAP: 4n/400nF, $\pm 4.0\%$

FREQ: 40/400kHz, $\pm 3.0\%$

Audible continuity, diode test

Battery: 9Vx1, 6F22

Dimensions & weight: 191x82x36mm, ~280g

Accessories: holster, clampjaw for AC/DC big current (optional)



REF: 0111155000

✓ CE (EMC), UL, CE (LVD)