

MS8220R True RMS HIGH SAFETY DMM WITH INTERFACE

- 6000 counts LCD display, SMT application
- RS232 interface to computer
- Data hold and LCD backlit
- Max/Min value measurement
- Auto/manual ranging, auto poweroff
- Secondary injection molding case, safety as per IEC1010-1 CAT.III 1000V

Technical specifications

DCV: 6/60/600/1000V, $\pm 0.5\%$

ACV: 6/60/600/700V, $\pm 0.8\%$

DCA: 600 /6m/60m/600m/10A, $\pm 1.2\%$

ACA: 600 /6m/60m/600m/10A, $\pm 1.5\%$

OHM: 600/6k/60k/600k/6M/60M, $\pm 1.0\%$

CAP: 6n/60n/600n/6 /60 /600 /6mF, $\pm 1.0\%$

FREQ: 6k/60k/600k/6M/60MHz, $\pm 0.5\%$

TEMP: $-40^{\circ}\text{C}\sim 1000^{\circ}\text{C}$, $-40^{\circ}\text{F}\sim 1832^{\circ}\text{F}$, $\pm 2.0\%$

Audible continuity, diode test

Battery: 9Vx1, 6F22

Dimensions & weight: 195x92x43mm, ~380g

Accessories: multi-function socket



REF: 018220R0000

✓ CE (EMC), UL, CE (LVD)

Sinometer