

MS8221

DMM WITH 2000AAC/DC
CURRENT MEASUREMENT



REF: 018221X0000

✓ CE (EMC), CE (LVD)

- Pocket size, 2000 counts LCD display
- Data hold & LCD backlit for easy reading
- Auto/manual ranging, auto-power off
- Max./Min. value measurement
- Measures 2000AAC/DC current using external transducer (optional)
- Battery test, temperature measurement
- Secondary injection molding housing, safety conforms to IEC1010 CAT.III 600V

Technical specifications

DCV: 200m/2/20/200/600V, $\pm 0.6\%$

ACV: 200m/2/20/200/600V, $\pm 0.7\%$

DCA: 200 μ /2m/20m/200m/2/10A, $\pm 1.2\%$
200/2000A (0.1mV/0.1A), $\pm 1.2\%$

ACA: 200 μ /2m/20m/200m/2/10A, $\pm 1.5\%$
200/2000A (0.1mV/0.1A), $\pm 1.5\%$

OHM: 200/2k/20k/200k/2M/20M, $\pm 1.2\%$

TEMP: -20 to 1000 /0~1800 $^{\circ}$ F, $\pm 3.0\%$

BATT: 1.5V(60mA), 3V(30mA), 9V(12mA)

Audible continuity & diode test

Transistor h_{FE} test: 0~1000

Battery: 1.5Vx3, AAAsize

Dimensions & weight: 158x74x31mm, ~220g

Accessories: temp. probe
current transducer (optional)

Sinometer