

MS8226

HIGH SAFETY DMM WITH INTERFACE

- 4000 counts LCD display, max. reading 3999
- Data hold & LCD backlit
- Relative measurement
- RS232C interface to computer
- Auto/manual ranging, auto poweroff
- Secondary injection molding case, safety as per IEC1010-1 CAT.III 1000V

Technical specifications

DCV: 400m/4/40/400/1000V, $\pm 0.5\%$

ACV: 4/40/400/700V, $\pm 0.8\%$

DCA: 400 /4m/40m/400m/10A, $\pm 1.2\%$

ACA: 400 /4m/40m/400m/10A, $\pm 1.5\%$

OHM: 400/4k/40k/400k/4M/40M, $\pm 1.0\%$

CAP: 40n/400n/4 /40 /100 F, $\pm 3.0\%$

FREQ: 4/40/400/4k/40kHz, $\pm 0.2\%$

TEMP: $-20^{\circ}\text{C} \sim 1000^{\circ}\text{C}$, $\pm 3.0\%$

Duty Cycle: 0.1%~99.9%, $\pm 4.0\%$

Audible continuity, diode test

Battery: 9Vx1, 6F22

Dimensions & weight: 195x92x43mm, ~380g

Accessories: temp. probe, multi-function socket



REF: 018226X0000

✓ CE (EMC), UL, CE (LVD)

Shometer