

MS8229 (5 IN 1)

DMM WITH MULTISENSOR INPUT



- 2000 counts digital multimeter with multisensor input for temp., humidity, lux, sound level measurements
- **LED indication of input sockets** when a range is set, and **sound/LED warning** if input to the wrong sockets
- Data hold & LCD backlight
- Maximum value measurement
- Auto/manual ranging, auto power off
- Safety as per IEC1010-1 Cat.III 600V & Cat.II 1000V

Technical Specifications

DCV: 200m/2/20/200/1000V, $\pm 0.7\%$

ACV: 200m/2/20/200/750V, $\pm 0.8\%$

DCmV: 20m/200mV, $\pm 0.7\%$

ACmV: 20m/200mV, $\pm 0.8\%$

DCA: 200 μ /2m/20m/200m/2/10A, $\pm 1.2\%$

ACA: 200 μ /2m/20m/200m/2/10A, $\pm 1.5\%$

OHM: 200/2k/20k/200k/2M/20M Ω , $\pm 1.0\%$

TEMP: $-20^{\circ}\text{C} \sim 1000^{\circ}\text{C}$ ($0 \sim 1800^{\circ}\text{F}$), $\pm 3.0\%$

TEMP (NTC): $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ ($32^{\circ}\text{F} \sim 104^{\circ}\text{F}$), $\pm 2^{\circ}\text{C}/4^{\circ}\text{F}$

%RH: 20%~95%, $\pm 5.0\%$ RH

LUX: 2,000/20,000Lux, $\pm 5.0\%$

SOUND dB: 40~100dB, $\pm 5.0\text{dB}$

Audible continuity & diode test

Dimensions: 195x92x55mm, ~ 400g

Battery: 1.5Vx3, AAA size



Sinometer

REF. 0108229X0000

✓ CE (EMC), □ UL, □ CE (LVD)

