



## MS8260C

HIGH SAFETY DMM with NCV

- 3 1/2 digits LCD display with backlit
- **Non-contact AC voltage detection (NCV)**
- 10A fused and full overload protection
- Data hold, auto power-off
- Elegant design with integrated holster
- Safety as per IEC1010-1, Cat.III 1000V & Cat.IV 600V

### Technical specifications

DCV: 200m/2/20/200/1000V,  $\pm 0.5\%$

ACV: 2/20/200/750V,  $\pm 0.8\%$

DCA: 20m/200m/10A,  $\pm 1.0\%$

ACA: 20m/200m/10A,  $\pm 1.0\%$

OHM: 200/2k/20k/200k/2M/20M/200M  $\Omega$ ,  $\pm 1.0\%$

CAP: 20n/200n/2 $\mu$ /200 $\mu$ F,  $\pm 3.0\%$

FREQ: 20kHz,  $\pm 3.0\%$

TEMP: -20°C ~ 1000°C,  $\pm 3.0\%$

NCV: >50V AC (TRMS)

Audible continuity and diode test

Tansistor  $h_{FE}$  test: 0~1000

Battery: 9Vx1, 6F22

Dimensions: 188x92x50mm

Accessories: k-type temp probe

REF: 018260C0000

CE (EMC),  UL,  CE (LVD)

**Sinometer**