



ST35

POCKET AUTO RANGING DMM

- Pocket size, 4000 counts LCD display
- Capacitance, temperature, frequency and duty cycle measurement
- Data hold for easy reading
- Auto ranging, auto power-off
- Secondary injection molding housing, safety conforms to IEC1010 CAT.III 600V

Technical specifications

DCV: 400m/4/40/400/600V, $\pm 0.5\%$

ACV: 4/40/400/600V, $\pm 1.2\%$

DCA: 400 μ /4m/40m/400m/4/10A, $\pm 1.8\%$

ACA: 400 μ /4m/40m/400m/4/10A, $\pm 3.0\%$

OHM: 400/4k/40k/400k/4M/40M Ω , $\pm 1.0\%$

CAP: 50n/500n/5 μ /50 μ /100 μ F, $\pm 4.0\%$

TEMP: -55°C ~ 800°C, $\pm 3.5\%$

FREQ: 10/100/1k/10k/100kHz, $\pm 1.5\%$

Duty cycle: 20%~80%, $\pm 3.5\%$

Audible continuity(<50 Ω) and diode test

Battery: 1.5Vx2, AAA size

Dimensions: 144x70x40mm

Weight: approx. 280g

REF: 01ST35X0000

☑ CE (EMC), ☐ UL, ☐ CE (LVD)

Sinometer