

VC8145B True RMS

TRUE RMS BENCH DIGITAL MULTIMETER



- 33,000 counts, dual 4 3/4 digits LCD with backlit , displays two parameters of input signal simultaneously
- Frequency measurement up to 30M Hz and 10 μ V voltage sensitivity
- Fast /Slow mode switch: 6~7 rdg/s or 3 rdg/s
- Self-calibration by user using front panel
- **True RMS** AC measurement, frequency response to 50kHz
- Max , Min, average value and relative measurement
- Comparison measurement
- Auto data hold, **USB interface** to computer
- Safety as per IEC1010-1, CAT.II 1000V

Technical specifications

DCV: 300m/3/30/300/1000V, $\pm 0.03\%$ (10M)

ACV: 300m/3/30/300/750V, $\pm 0.5\%$ (20~50k Hz)

DCA: 0.3m/3m/30m/300m/10A, $\pm 0.05\%$

ACA: 30m/300m/10A, $\pm 0.5\%$ (20~30k Hz)

OHM: 300/3k/30k/300k/3M/30M/100M , $\pm 0.05\%$

FREQ: 300/3k/30k/300K/3M/30MHz, $\pm 0.05\%$

dBm: impedance 50/75/93/110/125/135

/150 /250/300/500/600/800/900

/1000/1200 , ± 0.05 dBm

Power supply: AC 110V or 220V, $\pm 10\%$, 50/60Hz, 5VA

Dimensions: 245x220x82mm

Weight: approx. 2kgs



REF: 018145B0000

✓ CE (EMC), UL, CE (LVD)